

Introduction

The LogiCORE™ IP SelectIO™ Interface Wizard simplifies the integration of the SelectIO technology into the system design in the Spartan®-6 and Spartan-6 Lower Power devices. The Wizard creates an HDL file (Verilog or VHDL) that instantiates and configures I/O logic such as IOSERDES and IODELAY blocks configured to customer requirements. Additionally, it instantiates and configures the desired I/O clock primitive, connecting to the instantiated I/O logic.

Features

- Supports input, output or directional busses
- Creates clock circuitry required to drive I/O logic
- Supports up to a 32-bit wide data bus
- Supports optional data serialization of up to 8 bits
- Supports optional data and/or clock delay insertion
- Supports single and double data rate data
- Supports single-ended or differential standards for both clock and or data
- Provides an optional interface to implement phase detector functionality
- Provides access to optional primitive ports
- Output can be pulled into PlanAhead™ design tools for further I/O attribute setting
- Provides synthesizable example design and demonstration test bench to help with integration

LogiCORE IP Facts				
Core Specifics				
Supported Device Family	Spartan®-6 Spartan-6 -1L			
Resources Used	I/O	LUTs	FFs	Block RAMs
	1-33	0	0-16	0
Special Features	Depending on user selection 0-18 IODELAY2, 0-32 IOSERDES2, 0-32 OSERDES2, 0-16 ODDR, 0-16 IDDR, 0-2 BUFIO2, 0-1 BUFPLL, 1-3 BUFG			
Provided with Core				
Documentation	Product Brief Getting Started Guide			
Design File Formats	Verilog, VHDL			
Verification	Verilog, VHDL Test Bench			
Instantiation Template	Verilog, VHDL Wrapper			
Design Tool Requirements				
Xilinx Implementation Tools	ISE® 11.4			
Verification	Mentor Graphics ModelSim v6.4b and above, Cadence IUS v81 -s009 and above, Synopsys VCS and VCS MX 2008.09 and above Xilinx® ISIM			
Simulation	Mentor Graphics ModelSim v6.4b and above Cadence IUS v81 -s009 and above Synopsys VCS and VCS MX 2008.09 and above Xilinx® ISIM			
Synthesis	ISE tools, XST			
Support				
Provided by Xilinx, Inc.				

Ordering Information

This SelectIO Interface Wizard is provided under the [SignOnce IP Site License](#).

Revision History

The following table shows the revision history for this document:

Date	Version	Description of Revisions
09/16/09	1.1	Initial Xilinx release.
12/02/09	1.2	Added Spartan-6 -1L (Lower Power) device support.

Notice of Disclaimer

Xilinx is providing this product documentation, hereinafter "Information," to you "AS IS" with no warranty of any kind, express or implied. Xilinx makes no representation that the Information, or any particular implementation thereof, is free from any claims of infringement. You are responsible for obtaining any rights you may require for any implementation based on the Information. All specifications are subject to change without notice. XILINX EXPRESSLY DISCLAIMS ANY WARRANTY WHATSOEVER WITH RESPECT TO THE ADEQUACY OF THE INFORMATION OR ANY IMPLEMENTATION BASED THEREON, INCLUDING BUT NOT LIMITED TO ANY WARRANTIES OR REPRESENTATIONS THAT THIS IMPLEMENTATION IS FREE FROM CLAIMS OF INFRINGEMENT AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Except as stated herein, none of the Information may be copied, reproduced, distributed, republished, downloaded, displayed, posted, or transmitted in any form or by any means including, but not limited to, electronic, mechanical, photocopying, recording, or otherwise, without the prior written consent.